
Installation/Usage Instructions for CVC Series Concentric Vent Caps

Models: CVC-I2, CVC-R2, CVC-I3, CVC-R3

Before proceeding with the installation of your new vent cap, please read these instructions thoroughly. When handling, installing or removing any vent cap, always wear safety glasses.

Step 1: Turn off the high efficiency appliance so the concentric vent you are installing the cap on is not active.

Step 2: Wipe the concentric vent's exhaust pipe with a damp cloth to remove any dirt and debris.

Step 3: Carefully loosen each cone point set screw on the cap so they do not extend beyond the inside surface of the cap. Do not remove the set screws! The set screws are small and are designed to not extend beyond the outer surface of the installed cap where they would otherwise collect debris.

Step 4: Slide the cap over the concentric vent's exhaust pipe, making sure the small weep hole in front of the screen is pointed down in horizontal applications. This weep hole will aid in allowing condensate and rain to drip from the cap.

Step 5: Tighten each set screw, with the supplied hex wrench, until they just come into contact with the plastic on the concentric vent's exhaust pipe. Once all set screws have made contact, tighten each set screw 1/8 of a turn so the cone points lock the cap onto the concentric vent. Do not over-tighten the set screws as doing so may damage the threads on the cap or the concentric vent.

Step 6: Return the high efficiency appliance to the on position and test its operation.

Note: CVC-I (70% airflow insect) series vent caps are designed to protect concentric vents from insects during spring, summer and fall. In sub-freezing temperatures, and throughout winter, the CVC-R (90% airflow rodent) series vent caps must be used. Before installing any vent screen product, please consult your high efficiency appliance manufacturer to determine suitability.