

PVC Vent Screens

American Made Vent Protection Products

<https://pvcventscreens.com>

Tel: 440-679-4759

26787 Driscoll Ln.

North Olmsted, OH 44070

Installation/Usage Instructions for PVS Series PVC Vent Screens

Models: PVS-IS2, PVS-RS2, PVS-IS3, PVS-RS3, PVS-IS4, PVS-RS4

Before proceeding with the installation of your new PVC vent screen(s), please read these instructions thoroughly. When handling, installing or removing our vent screens, including the internal wire clip, please wear safety glasses at all times.

Step 1: Turn off the high efficiency appliance so that the vents you are installing the PVC vent screens on are not active.

Step 2: Wipe the inside of the PVC vent hub with a damp cloth to remove any dust or debris that may impede proper fitment of your new PVC vent screen.

Step 3: Carefully insert the PVC vent screen into the PVC vent until it seats flush against the flange. If needed, the PVC vent screen can be held in place with a common household clothespin.

Step 4: Take one end of the wire clip and insert it into the flange so that it is firmly against the PVC vent screen shell (installed in the shape of a "U"). Now take the other end of the wire clip and repeat this step, while also sliding in the lower part of the wire clip with your thumb so that it conforms to the inside of the hub. Once installed, please make sure that both ends of the wire clips are firmly against the PVC vent screen shell in addition to the bottom of the wire clip. Properly installed wire clips will rest against the outer vent screen shell and not obstruct airflow from the stainless steel mesh screen.

An installation video is also available for viewing on our website at <http://pvcventscreens.com/installation-video/> to aid in the installation process. Once the vent screen is properly installed, it will look like the image to the right.



Step 5: Return the high efficiency appliance to the on position and test its operation.

Note: Ideally, when you are completed with step 4 you will have three wire clip points of contact that will securely hold your PVC vent screen inside the PVC hub or coupling. Alternatively, caulk may be used but may require a clothespin to hold the PVC vent screen in place until the caulk fully cures.

Important: PVS-IS2, PVS-IS3 and PVS-IS4 series vent screen models are designed for insect and rodent protection during spring, summer and fall. Our rodent only vent screens are designed for winter use in regions where freezing temperatures occur. Before installing any vent screen product, please consult your high efficiency appliance manufacturer to determine suitability.